

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Polishers

L 602 VR

Order no. 329.800



Technical attributes	L 602 VR
Max. polishing pad diameter	220 mm
Max. back-up pad diameter	175 mm
No load speed	400-2400 rpm
Power input	1500 watt
Power output	1000 watt
Tool fixture	M 14
Weight	3,3 kg

Variable-speed polisher with a high torque

- VR electronics: stepless speed selection, constant speed control by means of tachogenerator, overload protection and temperature monitor
- Powerful 1500 watt motor with high degree of efficiency
- Integrated air deflection: protects against direct air flow
- Perfect cooling for heavy-duty use.
- Optimum handling by balanced weight distribution and 3 grip variants, depending on use
- Rubber rest bar protects machine and surface of workpiece when changing pads
- Spindle lock

Standard equipment	
1 side handle	252.721
1 bail handle	287.709

Accessories

SpecialPolish



Silicon-free, fine polishing compound for a high-degree of material removal and a medium gloss. For removing, for instance, ingrained dust, paint mists, fine scratches in combination with the lambswool. Together with the right sponge, ideally suited for removing signs of wear, restoring weathered paints.

Designation:	Contents:	QTY/PKG:	Order no.
P 05/03	250 ml	1	376.574

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Polishers

NanoPolish & Wax



Silicon-free, high-gloss polish with nano compound particles and carnauba wax. For polishing new to slightly scratched paints. Ideal for scratch-resistant paintwork. Also gives a perfect finish to paintwork pre-treated with the fine polishing compound. High-gloss finish and protection in one.

Designation:	Contents:	QTY/PKG:	Order no.
--------------	-----------	----------	-----------

P 02/06	250 ml	1	376.566
---------	--------	---	---------

Microfibre polishing cloth, premium



Thanks to the very high soft pile, residues can be picked up reliably and gently. This is what makes the microfibre cloth ideal for an optimum paint finish. It can also be used for car wash purposes. Long service life. washing machine safe (without softener).

Dimensions	QTY/PKG:	Order no.
------------	----------	-----------

in mm:

400 x 400	1	376.531
-----------	---	---------

Backed fleece



Fibre-back and M 14 threaded flange for removing scratches in glass, stainless steel, acrylic and high-gloss polishing of stainless steel. Use only with the respective polishing mediums.

Dimensions	QTY/PKG:	Order no.
------------	----------	-----------

in mm:

125 Ø	1	122.726
175 Ø	1	122.734

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Polishers

Velcro backing M 14



Elastic backing pad with velcro cover.

Dimensions in mm:	Designation:	QTY/PKG:	Order no.
125 Ø	Velcro bowl	1	231.983

Polishing sponge, blue



Sponge of a medium-hard, coarse foam structure and high resistance to tearing. With setback velour for assured polishing and as a centering aid. Particularly for weathered, dull paints and for scratches in combination with the SpecialPolish compound.

Designation:	Dimensions in mm:	QTY/PKG:	Order no.
PS-B 140	140 Ø x 30	1	376.388
PS-B 160	160 Ø x 30	1	376.396
PS-B 200	200 Ø x 30	1	376.418

Spare fleece



With fiber backing.

Dimensions in mm:	QTY/PKG:	Order no.
125 Ø	1	122.742
175 Ø	1	122.750

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Polishers

Polishing sponge, white



Sponge of a medium-hard, fine foam structure and highly resistant to tearing. With setback velour for assured polishing and as a centering aid. Particularly for removing minor traces of wear and streaks in combination with the SpecialPolish compound.

Designation:	Dimensions	QTY/PKG:	Order no.
in mm:			
PS-W 140	140 Ø x 30	1	376.426
PS-W 160	160 Ø x 30	1	376.434
PS-W 200	200 Ø x 30	1	376.442

Microfibre polishing cloth, classic



Seamless, washable. For gentle removing polishing and sealing residues. For a perfect surface finish and brilliant deep gloss.

Dimensions	Designation:	QTY/PKG:	Order no.
in mm:			
400 x 400	MW-C	1	317.098

Polishing sponge, black



Sponge of an extremely soft and fine foam structure. With setback velour for assured polishing and as a centering aid. Ideally suited - together with the SpecialPolish compound - for removing holograms and also for paint care and sealing in combination with the NanoPolish & Wax.

Designation:	Dimensions	QTY/PKG:	Order no.
in mm:			
PS-BL 140	140 Ø x 30	1	376.450
PS-BL 160	160 Ø x 30	1	376.469
PS-BL 200	200 Ø x 30	1	376.477

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Polishers

Polishing sponge wafer, black



Wafer sponge of an extremely soft and fine foam structure. The special PerfectTouch sandwich design and extra firm white foam layer give the pad much more stiffness and it does not compress so easily. As a result, holograms and micro-scratches, in particular, can be more efficiently and reliably removed. The special design also extends the service life of the polishing disc. With setback velour for assured polishing and as a centering aid. Ideally suited - together with the SpecialPolish compound - for removing holograms and also for paint care and sealing in combination with the NanoPolish & Wax.

Designation: Dimensions QTY/PKG: Order no.
in mm:

PSW-BL 140	140 Ø x 30	1	376.485
PSW-BL 160	160 Ø x 30	1	376.493
PSW-BL 200	200 Ø x 30	1	376.507

Velcro pad, cushioned M14



12 mm cell rubber for even pressure distribution for grinding, polishing or sealing.

Dimensions QTY/PKG: Order no.
in mm:

125 Ø	1	350.737
150 Ø	1	350.745

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Polishers

Velcro backed, classic



The pad consists of 90 % lambswool and 10 % polyester. This composition provides for more stability and volume. For great polishing effect in combination with the SpecialPolish.

Designation:	Dimensions	QTY/PKG:	Order no.
	in mm:		

TW-C 150	150 Ø	1	342.521
TW-C 200	200 Ø	1	350.265

Polishing lambswool, premium



Polishing lambswool consisting of 90% natural wool and 10% polyester. This combination provides for longer service life and greater volume. And it can remove sanding scratches, for example, 30% faster than with using a sponge. Ideal for UV paints and the latest generation of scratch-resistant paints. For a great polishing effect in combination with the SpecialPolish. The special PerfectTouch sandwich design and extra orange foam layer gives the pad that slight degree of cushioning and much greater stiffness. This allows for a perfect surface contact even in problem areas and an optimal and exact guiding.

Designation:	Dimensions	QTY/PKG:	Order no.
	in mm:		

TW-PT 140	140 Ø	1	376.515
TW-PT 160	160 Ø	1	376.523

Flexible backing pad



Backing pad from cellular rubber with rounded edges, for lambswool bonnet. Ensures for even pressure when polishing. M14 thread.

Dimensions	QTY/PKG:	Order no.
in mm:		

175 Ø	1	123.862
-------	---	---------

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Polishers

Lambswool bonnet



With tightening cord, suitable for elastic backing pad. Made of high-quality lambswool for efficient processing of polishing pastes.

Dimensions	QTY/PKG:	Order no.
------------	----------	-----------

in mm:

180 Ø	1	123.870
-------	---	---------